

## Specifications

<b>Processor</b>	AMD LX-700
<b>Memory</b>	Standard 512MB (expandable to 1GB), DDR SDRAM SO-DIMM x 1
<b>VGA Memory</b>	Default 8MB, expandable to 254MB, shares memory with system memory
<b>Power Supply</b>	12V DC Power Adaptor, 42W
<b>Housing</b>	Plastic & steel
<b>Speaker</b>	Built-in
<b>OS Support</b>	Microsoft® WIN CE 5.0 / WEPOS
<b>Safety Certifications</b>	FCC-A, CE-A
<b>Display</b>	
<b>LCD</b>	15" LCD, 250 nits, 1024 x 768 mirror, display mode supported
<b>Touch Sensor</b>	Resistive
<b>Touch Controller</b>	USB interface mouse emulation
<b>Brightness Control</b>	Hardware VR control
<b>Tilt Adjustment</b>	From 17.5° to 76.5°
<b>Expansion</b>	
<b>Storage Device</b>	CF memory card or HDD (cannot co-exist)
<b>Mounting Options</b>	Desktop / wallmount (option)
<b>Connectivity</b>	
<b>Audio Port</b>	2 Watt AUDIO output with built-in speaker; Mic. In/Line Out ports available when optional SD-400 installed
<b>Compact Flash Port (Type II, memory card only)</b>	Standard
<b>CR Port</b>	N/A
<b>KB Port</b>	1 x, P/S II
<b>LAN Port</b>	1 x, 10/100 Base T Ethernet
<b>PS/2 Mouse Port</b>	N/A
<b>Parallel Port</b>	1 x, SPP/EPP/ECP
<b>Serial Port</b>	2 x RS-232 connectors, each with +5V power supply
<b>UPS Port</b>	N/A
<b>USB Port</b>	4 x, USB 2.0 + 1 proprietary port for SD-400
<b>Environment</b>	
<b>Operation Condition</b>	0°C~+35°C (32°F~+95°F), 20%RH~80%RH, non-condensing max wet bulb 26°C (78.8°F)
<b>Storage Condition</b>	20°C~+60°C (4°F~+140°F) without UPS battery, -20°C~+40°C (-4°F~+104°F) with UPS battery, 10%RH~80%RH, non-condensing max, wet bulb 28.9°C (84.0°F)
<b>Optional Accessories</b>	
<b>2nd LCD Display</b>	12" LM6101B or VGA Port
<b>Customer Pole Display</b>	PD2501: 11mm VFD display, 5x7 dot matrix, RS232 interface PD2602: 2x20 VFD display, 5x7 dot matrix, default RS232 interface, optional USB interface
<b>Preloaded OS</b>	Microsoft WIN XP / WEPOS / WIN CE
<b>SD-400 Magnetic Stripe Reader</b>	Optional 2-track or 3-track MSR with/without Finger Print Sensor
<b>UPS Battery</b>	N/A